



**15NM80-Q****Power MOSFET****15A, 800V N-CHANNEL
SUPER-JUNCTION MOSFET****DESCRIPTION**

The **UTC 15NM80-Q** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at AC-DC converters for power applications.

FEATURES

- * $R_{DS(ON)} \leq 0.48 \Omega$ @ $V_{GS}=10V$, $I_D=5.0A$
- * Fast switching capability
- * Avalanche energy tested
- * Improved dv/dt capability, high ruggedness

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment					Packing
Lead Free	Halogen Free		1	2	3	4	5	
15NM80L-TF1-T	15NM80G-TF1-T	TO-220F1	G	D	S	-	-	Tube
15NM80L-TF3-T	15NM80G-TF3-T	TO-220F	G	D	S	-	-	Tube
15NM80L-TQ2-T	15NM80G-TQ2-T	TO-263	G	D	S	-	-	Tube
15NM80L-TQ2-R	15NM80G-TQ2-R	TO-263	G	D	S	-	-	Tape Reel
15NM80L-K04-8080-R	15NM80G-K04-8080-R	DFN8080-4	G	S	S	S	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

15NM80G-TF1-T		(1)Packing Type	(1) T: Tube, R: Tape Reel (2) TF1: TO-220F1, TF3: TO-220F, TQ2: TO-263 K04-8080: DFN8080-4 (3) G: Halogen Free and Lead Free, L: Lead Free
		(2)Package Type	
		(3)Green Package	

MARKING

TO-220F / TO-220F1 / TO-263	DFN8080-4
UTC 15NM80 Lot Code 1 Date Code L: Lead Free G: Halogen Free	UTC 15NM80 Lot Code Date Code

■ **ABSOLUTE MAXIMUM RATINGS** ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER			SYMBOL	RATINGS	UNIT
Drain-Source Voltage			V _{DSS}	800	V
Gate-Source Voltage			V _{GSS}	±30	V
Drain Current	Continuous	T _C =25°C	I _D	15	A
		T _C =100°C		9.75	A
	Pulsed (Note 2)		I _{DM}	45	A
Avalanche Energy	Single Pulsed (Note 3)		E _{AS}	480	mJ
MOSFET dv/dt ruggedness			dv/dt	50	V/ns
Peak Diode Recovery dv/dt (Note 4)				1.9	V/ns
Power Dissipation	TO-220F/TO-220F1		P _D	29	W
	TO-263			90	W
	DFN8080-4			58	W
Junction Temperature			T _J	+150	°C
Storage Temperature			T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 100\text{mH}$, $I_{AS} = 3.1\text{A}$, $V_{DD} = 90\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq 15\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220F/TO-220F1	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$
	TO-263			
	DFN8080-4		35 (Note)	$^{\circ}\text{C}/\text{W}$
Junction to Case	TO-220F/TO-220F1	θ_{JC}	4.31	$^{\circ}\text{C}/\text{W}$
	TO-263		1.39 (Note)	$^{\circ}\text{C}/\text{W}$
	DFN8080-4		2.15 (Note)	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate P_c board, 2oz copper, with 1inch square copper plate.


■ **ELECTRICAL CHARACTERISTICS** ($T_J=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	800			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =800V, V _{GS} =0V			10	μA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±30V, V _{DS} =0V			±100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.5		4.5	V
Static Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =5.0A		0.43	0.48	Ω
DYNAMIC CHARACTERISTICS						
Input Capacitance	C _{ISS}	V _{GS} =0V, V _{DS} =50V, f=1MHz		970		pF
Output Capacitance	C _{OSS}			123		pF
Reverse Transfer Capacitance	C _{RSS}			5.2		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge	Q _G	V _{DS} =640V, V _{GS} =10V, I _D =15A (Note 1, 2)		50		nC
Gate-Source Charge	Q _{GS}			13		nC
Gate-Drain Charge	Q _{DD}			19		nC
Turn-On Delay Time	t _{D(ON)}	V _{DD} =100V, V _{GS} =10V, I _D =15A, R _G =25Ω (Note 1, 2)		14		ns
Turn-On Rise Time	t _R			25		ns
Turn-Off Delay Time	t _{D(OFF)}			110		ns
Turn-Off Fall Time	t _F			45		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Continuous Drain-Source Diode Forward Current	I _S				15	A
Maximum Pulsed Drain-Source Diode Forward Current	I _{SM}				45	A
Drain-Source Diode Forward Voltage	V _{SD}	I _S =5.0A, V _{GS} =0V			1.4	V
Body Diode Reverse Recovery Time	t _{rr}	I _S =15A, V _{GS} =0V,		488		nS
Body Diode Reverse Recovery Charge	Q _{rr}	dI _F /dt=100A/μs		8.2		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Charge
Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms



■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.