



26NM60Z-U3

Power MOSFET


26A, 600V N-CHANNEL SUPER-JUNCTION MOSFET

DESCRIPTION


The **UTC 26NM60Z-U3** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at AC-DC converters for power applications.

FEATURES

- * $R_{DS(ON)} \leq 0.15 \Omega$ @ $V_{GS}=10V$, $I_D=6.5A$
- * Fast switching capability
- * Avalanche energy tested
- * Improved dv/dt capability, high ruggedness
- * With ESD Protected: HBM=2KV



SYMBOL



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment									Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	9	
26NM60ZL-U3-TA3-T	26NM60ZG-U3-TA3-T	TO-220	G	D	S	-	-	-	-	-	-	Tube
26NM60ZL-U3-TF1-T	26NM60ZG-U3-TF1-T	TO-220F1	G	D	S	-	-	-	-	-	-	Tube
26NM60ZL-U3-TW1-T	26NM60ZG-U3-TW1-T	TO-220WF	G	D	S	-	-	-	-	-	-	Tube
26NM60ZL-U3-T47-T	26NM60ZG-U3-T47-T	TO-247	G	D	S	-	-	-	-	-	-	Tube
26NM60ZL-U3-T8B-R	26NM60ZG-U3-T8B-R	TOLL-8B	G	S	S	S	S	S	S	S	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

26NM60ZG-U3-TA3-T (1) Packing Type (2) Package Type (3) Version Code (4) Green Package	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF1: TO-220F1, TW1: TO-220WF T47: TO-247, T8B: TOLL-8B (3) Version U3 (4) G: Halogen Free and Lead Free, L: Lead Free
--	---

MARKING

TO-220 / TO-220F1 / TO-220WF / TO-247	TOLL-8B
UTC 26NM60Z U3 1 Version Code Lot Code Date Code L: Lead Free G: Halogen Free	UTC 26NM60Z U3 1 Version Code Lot Code Date Code L: Lead Free G: Halogen Free

■ **ABSOLUTE MAXIMUM RATINGS** ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	600	V
Gate-Source Voltage		V_{GSS}	± 20	V
Drain Current	Continuous	I_D	26	A
	Pulsed (Note 2)	I_{DM}	78	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	62.5	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	1.2	V/ns
Power Dissipation	TO-220	P_D	115	W
	TO-220F1/TO-220WF		33	W
	TO-247		130	W
	TOLL-8B		200	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 10\text{mH}$, $I_{AS} = 3.5\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\Omega$ Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq 26\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220 /TO-220F1	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$
	TO-220WF			
	TO-247		40	$^{\circ}\text{C}/\text{W}$
	TOLL-8B		35 (Note)	$^{\circ}\text{C}/\text{W}$
Junction to Case	TO-220	θ_{JC}	1.08	$^{\circ}\text{C}/\text{W}$
	TO-220F1/TO-220WF		3.79	$^{\circ}\text{C}/\text{W}$
	TO-247		0.96	$^{\circ}\text{C}/\text{W}$
	TOLL-8B		0.625 (Note)	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.


■ **ELECTRICAL CHARACTERISTICS** ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	600			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =600V, V _{GS} =0V			1	μA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±10	μA
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	3.0		4.5	V
Static Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =6.5A			0.15	Ω
DYNAMIC CHARACTERISTICS						
Input Capacitance	C _{ISS}	V _{GS} =0V, V _{DS} =50V, f=1MHz		1400		pF
Output Capacitance	C _{OSS}			400		pF
Reverse Transfer Capacitance	C _{RSS}			14		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge (Note 1)	Q _G	V _{DS} =480V, V _{GS} =10V, I _D =13A (Note 1, 2)		52		nC
Gate-Source Charge	Q _{GS}			11		nC
Gate-Drain Charge	Q _{DD}			27		nC
Turn-On Delay Time (Note 1)	t _{D(ON)}	V _{DD} =100V, V _{GS} =10V, I _D =13A R _G =25Ω (Note 1, 2)		21		ns
Turn-On Rise Time	t _r			37		ns
Turn-Off Delay Time	t _{D(OFF)}			181		ns
Turn-Off Fall Time	t _f			77		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Continuous Drain-Source Diode Forward Current	I _S				26	A
Maximum Pulsed Drain-Source Diode Forward Current	I _{SM}				78	A
Drain-Source Diode Forward Voltage (Note 1)	V _{SD}	I _S =26A, V _{GS} =0V			1.4	V
Body Diode Reverse Recovery Time (Note 1)	t _{rr}	I _S =26A, V _{GS} =0V, dI _F /dt=100A/μs		404		nS
Body Diode Reverse Recovery Charge	Q _{rr}			6155		nC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Charge
Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms



TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (Cont.)



TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.