

BSS139Z

Power MOSFET

N-CHANNEL LOGIC LEVEL ENHANCEMENT MODE

■ DESCRIPTION

This device employs advanced MOSFET technology and features low gate charge while maintaining low on-resistance.

Optimized for switching applications, this device improves the overall efficiency of DC/DC converters and allows operation to higher switching frequencies.

■ FEATURES

* $R_{DS(ON)} \leq 1.8 \Omega$ @ $V_{GS}=10$ V, $I_D=0.22A$

$R_{DS(ON)} \leq 2.4 \Omega$ @ $V_{GS}=4.5V$, $I_D=0.22A$

$R_{DS(ON)} \leq 6.5 \Omega$ @ $V_{GS}=2.5V$, $I_D=0.20A$


* Low Capacitance

* Low Gate Charge

* Fast Switching Capability

* Avalanche Energy Specified

■ SYMBOL




■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
BSS139ZL-AE2-R	BSS139ZG-AE2-R	SOT-23-3	G	S	D	Tape Reel

Note: Pin Assignment: G: Gate S: Source D: Drain

 (1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel (2) AE2: SOT-23-3 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	50	V
Gate-Source Voltage	V_{GSS}	± 20	V
Continuous Drain Current	I_D	0.22	A
Pulse		0.88	A
Peak Diode Recovery dv/dt	dv/dt	4.8	V/ns
Power Dissipation	P_D	225	W
Junction Temperature	T_J	+150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	556	$^\circ\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.







■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0\text{V}, I_D=250\mu\text{A}$	50			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=50\text{V}, V_{GS}=0\text{V}$			1	μA
		$V_{DS}=30\text{V}, V_{GS}=0\text{V}$			0.5	μA
Gate-Body Leakage, Forward	I_{GSS}	$V_{DS}=0\text{V}, V_{GS}=\pm 20\text{V}$			± 10	μA
ON CHARACTERISTICS (Note)						
Gate-Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=1\text{mA}$	0.5	0.9	1.5	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10\text{V}, I_D=0.22\text{A}$		1.3	1.8	Ω
		$V_{GS}=4.5\text{V}, I_D=0.22\text{A}$		1.5	2.4	Ω
		$V_{GS}=2.5\text{V}, I_D=0.20\text{A}$		2.2	6.5	Ω
On-State Drain Current	$I_{D(ON)}$	$V_{GS}=10\text{V}, V_{DS}=5\text{V}$	0.2			A
DYNAMIC PARAMETERS						
Input Capacitance	C_{ISS}	$V_{DS}=25\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$		16.7		pF
Output Capacitance	C_{OSS}			10.2		pF
Reverse Transfer Capacitance	C_{RSS}			4.5		pF
SWITCHING PARAMETERS (Note)						
Total Gate Charge	Q_G	$V_{DS}=40\text{V}, V_{GS}=10\text{V}, I_D=0.22\text{A}$		8.2		nC
Gate Source Charge	Q_{GS}			1.1		nC
Gate Drain Charge	Q_{GD}			0.3		nC
Turn-ON Delay Time	$t_{D(ON)}$	$V_{DD}=30\text{V}, I_D=0.22\text{A}, V_{GS}=10\text{V}, R_G=6\Omega$		0.8		ns
Turn-ON Rise Time	t_R			16		ns
Turn-OFF Delay Time	$t_{D(OFF)}$			6.4		ns
Turn-OFF Fall-Time	t_F			13		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Max. Diode Forward Current	I_S	$V_{GS}=0\text{V}, I_S=0.44\text{A}$			0.22	A
Drain-Source Diode Forward Voltage	V_{SD}			0.8	1.4	V
Reverse Recovery Time	t_{rr}		$V_{GS}=0\text{V}, I_S=0.22\text{A}, dI/dt=100\text{A}/\mu\text{s}$	18		ns
Reverse Recovery Charge	Q_{rr}			12		nC







Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.


■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



- TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.