



CD4069C

CMOS IC

INVERTER CIRCUITS


■ DESCRIPTION

The UTC **CD4069C** consists of three inverter circuits and is manufactured using complementary MOS (CMOS) to achieve wide power supply operating range, low power consumption, high noise immunity, and symmetric controlled rise and fall times.

All inputs are protected from damage due to static discharge by diode clamps to V_{DD} and V_{SS} .

■ FEATURES


- * Wide supply voltage range: 3.0V ~ 15V.
- * High noise immunity: 0.45 V_{DD} typ.
- * Low Power TTL compatibility: Fan out of 2 driving U74L or 1 driving U74LS.




SOP-8

■ ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen-Free		
CD4069CL-S08-R	CD4069CG-S08-R	SOP-8	Tape Reel

CD4069CG-S08-R 		(1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel (2) S08: SOP-8 (3) G: Halogen Free and Lead Free, L: Lead Free
---	--	--	---


■ MARKING



■ PIN CONFIGURATION



■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
DC Supply Voltage	V_{DD}	-0.5 ~ +18	V
Input Voltage	V_{IN}	-0.5 ~ V_{DD} +0.5	V
Storage Temperature Range	T_S	-65 ~ +150	°C
Junction Temperature	T_J	+150	°C
Operating Temperature	T_{OPR}	-40 ~ +125	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS ($V_{SS}=0V$)

PARAMETER	SYMBOL	RATINGS	UNIT
DC Supply Voltage	V_{DD}	3 ~ 15	V
Input Voltage	V_{IN}	0 ~ V_{DD}	V

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	150	°C/W

■ DC ELECTRICAL CHARACTERISTICS ($V_{SS}=0V$, $T_A=25^\circ C$, unless otherwise specified.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Quiescent Device Current	I_{DD}	$V_{DD}=5V$, $V_{IN}=V_{DD}$ or V_{SS}			1.0	μA
		$V_{DD}=10V$, $V_{IN}=V_{DD}$ or V_{SS}			2.0	μA
		$V_{DD}=15V$, $V_{IN}=V_{DD}$ or V_{SS}			4.0	μA
Low Level Output Voltage	V_{OL}	$ I_O < 1\mu A$, $V_{DD}=5V$		0	0.05	V
		$ I_O < 1\mu A$, $V_{DD}=10V$		0	0.05	V
		$ I_O < 1\mu A$, $V_{DD}=15V$		0	0.05	V
High Level Output Voltage	V_{OH}	$ I_O < 1\mu A$, $V_{DD}=5V$	4.95			V
		$ I_O < 1\mu A$, $V_{DD}=10V$	9.95			V
		$ I_O < 1\mu A$, $V_{DD}=15V$	14.95			V
Low Level Input Voltage	V_{IL}	$ I_O < 1\mu A$, $V_{DD}=5V$, $V_O=4.5V$			1.0	V
		$ I_O < 1\mu A$, $V_{DD}=10V$, $V_O=9V$			2.0	V
		$ I_O < 1\mu A$, $V_{DD}=15V$, $V_O=13.5V$			3.0	V
High Level Input Voltage	V_{IH}	$ I_O < 1\mu A$, $V_{DD}=5V$, $V_O=0.5V$	4.0			V
		$ I_O < 1\mu A$, $V_{DD}=10V$, $V_O=1V$	8.0			V
		$ I_O < 1\mu A$, $V_{DD}=15V$, $V_O=1.5V$	12.0			V
Low Level Output Current (Note 2)	I_{OL}	$V_{DD}=5V$, $V_{OL}=0.4V$	0.44	0.88		mA
		$V_{DD}=10V$, $V_{OL}=0.5V$	1.1	2.25		mA
		$V_{DD}=15V$, $V_{OL}=1.5V$	3.0	8.8		mA
High Level Output Current (Note 2)	I_{OH}	$V_{DD}=5V$, $V_{OH}=4.6V$	-0.44	-0.88		mA
		$V_{DD}=10V$, $V_{OH}=9.5V$	-1.1	-2.25		mA
		$V_{DD}=15V$, $V_{OH}=13.5V$	-3.0	-8.8		mA
Input Current	I_{IN}	$V_{DD}=15V$, $V_{IN}=0V$			± 1	μA
		$V_{DD}=15V$, $V_{IN}=15V$			± 1	μA

■ AC ELECTRICAL CHARACTERISTICS (Note 1)

(T_A=25°C, C_L=50pF, R_L=200kΩ, t_R and t_F ≤ 20 ns, unless otherwise specified)


PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Propagation Delay Time from Input to Output	t _{PHL} or t _{PLH}	V _{DD} =5V		50	90	ns
		V _{DD} =10V		30	60	ns
		V _{DD} =15V		25	50	ns
Transition Time	t _{THL} or t _{TLH}	V _{DD} =5V		80	150	ns
		V _{DD} =10V		50	100	ns
		V _{DD} =15V		40	80	ns
Average Input Capacitance	C _{IN}	Any Gate		6	15	pF
Power Dissipation Capacitance	C _{PD}	Any Gate (Note 3)		12		pF

Notes: 1. AC Parameters are guaranteed by DC correlated testing.

2. I_{OH} and I_{OL} are tested one output at a time.


3. C_{PD} determines the no load AC power consumption of any CMOS device.

■ AC TEST CIRCUITS AND SWITCHING TIME WAVEFORMS




TYPICAL CHARACTERISTICS


Gate Transfer Characteristics




Power Dissipation vs Frequency




Propagation Delay vs Ambient Temperature



Propagation Delay vs Ambient Temperature



Propagation Delay Time vs Load Capacitance



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.