



DUAL NPN DIGITAL TRANSISTOR (BUILT- IN BIAS RESISTORS)


DESCRIPTION

The UTC **UMH24** is an dual transistor; it uses UTC's advanced technology to provide the customers with low collector -emitter saturation voltage, etc.

FEATURES

- * NPN silicon transistor (Built-in resistor type)
- * 100 mA output current capability
- * Built-in bias resistors
- * Simplifies circuit design
- * Reduces component count
- * Reduces pick and place costs

EQUIVALENT CIRCUIT




ORDERING INFORMATION


Ordering Number		Package	Pin Assignment						Packing
Lead Free	Halogen Free		1	2	3	4	5	6	
UMH24L-AL6-R	UMH24G-AL6-R	SOT-363	G1	I1	O2	G2	I2	O1	Tape Reel

Note: Pin Assignment: G: GND I: IN O: OUT

UMH24G-AL6-R	(1)Packing Type	(1) R: Tape Reel
	(2)Package Type	(2) AL6: SOT-363
	(3)Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free



■ MARKING



■ **ABSOLUTE MAXIMUM RATING** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	50	V
Emitter-Base Voltage	V_{EBO}	10	V
Input Voltage	V_{IN}	-40 ~ +10	V
Output Current	I_{OUT}	20	mA
Power Dissipation	P_C	300	mW
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Ambient Temperature	T_{amb}	-55 ~ +150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **THERMAL DATA**

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	417	$^{\circ}\text{C/W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.

■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}$, $I_E=0\text{A}$	50			V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=2\text{mA}$, $I_B=0\text{A}$	50			V
Collector-Base Cut-Off Current	I_{CBO}	$V_{CB}=50\text{V}$, $I_E=0\text{A}$			100	nA
Collector-Emitter Cut-Off Current	I_{CEO}	$V_{CE}=30\text{V}$, $I_B=0\text{A}$			100	nA
Emitter-Base Cut-Off Current	I_{EBO}	$V_{EB}=5\text{V}$, $I_C=0\text{A}$			50	μA
DC Current Gain	h_{FE}	$V_{CE}=5\text{V}$, $I_C=5\text{mA}$	80			
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=5\text{mA}$, $I_B=0.25\text{mA}$			150	mV
Off-State Input Voltage	$V_{I(OFF)}$	$V_{CE}=5\text{V}$, $I_C=100\mu\text{A}$			0.8	V
On-State Input Voltage	$V_{I(ON)}$	$V_{CE}=0.3\text{V}$, $I_C=1\text{mA}$	3			V
Bias Resistor 1 (Input)	R1		70	100	130	K Ω
Bias Resistor Ratio	R2/R1		0.8	1	1.2	
Collector Capacitance	C_C	$V_{CB}=10\text{V}$, $I_E=0\text{A}$, $f=1\text{MHz}$			2.5	pF
Transition Frequency	f_T	$V_{CE}=10\text{V}$, $I_E=-5\text{mA}$, $f=100\text{MHz}$ (Note)		250		MHz

Note: Transition frequency of the device.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.